



Drilling Capacity: 1,500' Portable Truck Mounted Drill Rig – California “carb Compliant” Equipment

Hydraulic Hoist: 50,000# Capacity

Mounting: Peterbilt Model 367, 6 X 4 Tandem Axle Carrier

Main Power: Cat, C15, Diesel, 550 Hp, Tier 3 With Eaton Fuller-8 Speed Transmission

Leveling Jacks: Four (4) Leveling Jacks: 2 With 48” Lift Mounted Behind Cab, 2 With 36” Lift Mounted At Rear

Mast: 35 Foot Height Above Break Out Table Rated 50,000# Pull Down Capacity: 25,000# Hold Back Capacity: 50,000#

Top Head: Gefco Hydraulic Top Drive 5,833 Ft/lbs Of Rotary Torque, 0-120 Rpm 29 Feet Of Travel

Compressor: Sullair 1150 Cfm @ 350 Psi, 2-stage Twin Screw Air Drilling Compressor

Centrifugal Pump: Mission Magnum Sandhandler, 4” X 3” X 13” Impeller Hydraulic Driven

Mud System: Tibban Manufacturing Mud Puppy, Model Mp170-2sc, Shaker With Double Screens; 2-5” Desander Cones; 600 Gallon Mud Tank With Mud Mix Hopper, With Sand Guzzler Lift Pump; Powered By Deutz 74 Hp Diesel, Tier 4 Emissions Compliant; Trailer Mounted

Air/fluid Piping: 3 Inch

Water Injection: 18 Gpm

Breakout Wrench: Hydraulically Controlled

Pipe Rack: Drill Pipe Storage Capacity-15 Joints, 4-1/2” X 20 Ft

Pipe Loader: Single Pipe Handler For Loading Of Drill Pipe

Fuel Tank: Truck Mounted 100 Gallon Capacity

Drill Pipe: 1500 Feet Of 4-1/2” X 2-7/8 Api If X 20’ Drill Pipe

Drill Tooling: 3-1/2” Dual Tube And 6” Dhh Available

Drill Collars: 6 And 8 Inch Od

Dimensions: Weight – 56,000# Dry; 59,000# Wet Width – 8’-6” Inches Length, Derrick Down – 35’-6”

